

Arrange your messy dates : : CHEAT SHEET



Basics

The package functions offer the user both **flexibility** and more **precision** when dealing with **uncertain dates**. It implements the extended annotation standard for dates, the Extended Date/Time Format (EDTF), outlined in **ISO 8601-2_2019(E)** for R.

These include standardised annotation with:

- "?" for date whose source is considered dubious
- "~" for approximate date
- "X" for unspecified date
- "[" for set of dates [2012-01-01, 2012-01-12] or ".." for ranges 2012-01-01..2012-01-12"

1. Coerce objects to `mdate` class

From three columns

```
make_messydate(year, month, day)
```

Year	Month	Day	Date	Class
2007	2	17	2007-02-17	mdate
2000	11	19	2000-11-19	mdate
1998	12	6	1998-12-06	mdate

From one column

```
as_messydate(date)
```

These functions coerce different dates classes into **'mdate' class**, so that other package functions may be applied. The function also converts text (character strings) to numeric dates in **'mdate' class**.

Date	Class
2007-XX-18	as.Date
2020-09-22	POSIXct
2017-04-11	POSIXlt
2021-04	character
2018	character
2021-01-XX	character
2012-09-12~	character
2008-01-18?	character
2012-01..2012-03	character
first june, two thousand	character



Date	Class
2007-XX-18	mdate
2020-09-22	mdate
2017-04-11	mdate
2021-04	mdate
2018	mdate
2021-01	mdate
2012-09-12~	mdate
2008-01-18?	mdate
2012-01..2012-03	mdate
2000-06-01	mdate

2. Explore all possible dates

Contract from all possible dates to one

```
contract(messydate)
```

"2021-04-01", "2021-04-02", ..., "2021-04-30" → "2021-04"
"2021-01-01", "2021-01-02", ..., "2021-12-31" → "2021"

Expand to all possible dates

```
expand(messydate)
```


Once the uncertain dates are in `mdate` class, `expand()` transform the **single uncertain** date to all **possible dates**. If the date is one year (e.g. 2021), `expand()` will give all 365 possible dates.

"2019-02-01..2019-02-03" → "2019-02-01", "2019-02-02", "2019-02-03"
"2021-04" → "2021-04-01", "2021-04-02", ..., "2021-04-29", "2021-04-30"
"2021" → "2021-01-01", "2021-01-02", "2021-01-03", ..., "2021-12-30", "2021-12-31"

3. Choose a date and coerce it from `mdate` class

```
as.Date(as_messydate(date))
```

Coerce back to a **date**, **POSIXct** or **POSIXlt** class while choosing an exact value from all possible dates. It can be either the **minimum**, **maximum**, **mean**, **median**, or even the **mode** or a **random** value.



as.Date(as_messydate("2021-04"), min) → "2021-04-01"
as.Date(as_messydate("2021-04"), max) → "2021-04-30"
as.Date(as_messydate("2021-04"), mean) → "2021-04-16"
as.Date(as_messydate("2021-04"), median) → "2021-04-16"
as.Date(as_messydate("2021-04"), random) → "2021-04-11"

Other package functionalities

1) Some datasets contains arbitrary cut-off because the real date is unknown. This set of functions allows to indicate that these are approximations

Functions	Messydates
on_or_before(1918-01-01)	...1918-01-01
on_or_after(2016-01-01)	2016-01-01...
add_approximation(1917-01-01)	~1917-01-01
add_uncertainty(2002-12-31)	?2002-12-31

2) These functions allows to join two vectors of messydates in specific ways

```
md_intersect(messydates, messydates)
```

```
md_union(messydates, messydates)
```

```
md_multiset(messydates, messydates)
```



3) The package contains several logical tests which check whether the object is in `mdate` class or if one element is intersecting, similar to or part of a vector of messydates

```
is_messydate(messydate)
```

4) Extract only the years, months or days from the vector of `mdate` class or get the level of precision of a messydate

```
year(messydates)
```

```
precision(messydates)
```