

# Package ‘broomExtra’

August 19, 2019

**Type** Package

**Title** Enhancements for 'broom' Package Family

**Version** 0.0.5

**Maintainer** Indrajeet Patil <patilindrajeet.science@gmail.com>

**Description** Collection of functions to assist 'broom' and 'broom.mixed' package-related data analysis workflows. In particular, the generic functions tidy(), glance(), and augment() choose appropriate S3 methods from these two packages depending on which package exports the needed method. Additionally, 'grouped\_' and 'boot\_' variants of the generics provides a convenient way to execute functions across a combination of grouping variable(s) in a dataframe or bootstrap them.

**License** GPL-3 | file LICENSE

**URL** <https://indrajeetpatil.github.io/broomExtra/>,  
<https://github.com/IndrajeetPatil/broomExtra>

**BugReports** <https://github.com/IndrajeetPatil/broomExtra/issues>

**Depends** R (>= 3.5.0)

**Imports** broom (>= 0.5.2),  
broom.mixed (>= 0.2.4),  
dplyr (>= 0.8.1),  
magrittr (>= 1.5),  
purrr (>= 0.3.2),  
rlang (>= 0.4.0),  
rsample (>= 0.0.4),  
tidyr (>= 0.8.3),  
utils

**Suggests** generics,  
ggplot2,  
knitr,  
lme4,  
rmarkdown,  
spelling,  
stringr,  
testthat

**VignetteBuilder** knitr

**Encoding** UTF-8

**Language** en-US

**LazyData** true

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 6.1.1.9000

## R topics documented:

augment . . . . .	2
boot_augment . . . . .	3
boot_glance . . . . .	4
boot_tidy . . . . .	6
glance . . . . .	7
grouped_augment . . . . .	8
grouped_glance . . . . .	9
grouped_tidy . . . . .	10
tidy . . . . .	12
<b>Index</b>	<b>13</b>

---

augment	<i>Retrieve augmented dataframe if it exists.</i>
---------	---

---

## Description

Check if a `augment` method exists for a given object, either in `broom` or in `broom.mixed`. If it does, return the model summary dataframe, if not, return a `NULL`.

## Usage

```
augment(x, ...)
```

## Arguments

<code>x</code>	Model object or other R object with information to append to observations.
<code>...</code>	Addition arguments to <code>augment</code> method.

## Value

A `tibble::tibble()` with information about data points.

## Methods

No methods found in currently loaded packages.

## Note

For available methods, see- [https://indrajeetpatil.github.io/broomExtra/articles/available\\_methods.html](https://indrajeetpatil.github.io/broomExtra/articles/available_methods.html)

**Author(s)**

Indrajeet Patil

**See Also**[grouped\\_augment](#), [boot\\_augment](#)**Examples**

```
set.seed(123)
library(lme4)

# mixed-effects models (`broom.mixed` will be used)
lmm.mod <- lmer(Reaction ~ Days + (Days | Subject), sleepstudy)
broomExtra::augment(lmm.mod)

# linear model (`broom` will be used)
lm.mod <- lm(Reaction ~ Days, sleepstudy)
broomExtra::augment(lm.mod)
```

---

boot_augment	<i>Bootstrapped dataframe with augmented predictions from each sample.</i>
--------------	--

---

**Description**

Bootstrapped dataframe with augmented predictions from each sample.

**Usage**

```
boot_augment(data, times = 25, strata = NULL, apparent = FALSE, ..f,
  ..., augment.args = list())
```

**Arguments**

data	Dataframe (or tibble) from which variables are to be taken.
times	The number of bootstrap samples.
strata	A variable that is used to conduct stratified sampling. When not NULL, each bootstrap sample is created within the stratification variable. This could be a single character value or a variable name that corresponds to a variable that exists in the data frame.
apparent	A logical. Should an extra resample be added where the analysis and holdout subset are the entire data set. This is required for some estimators used by the summary function that require the apparent error rate.
..f	A function, or function name as a string.
...	Arguments to function. These dots support <a href="#">tidy-dots</a> features.
augment.args	A list of arguments to be used in the relevant S3 method.

**Value**

A `tibble::tibble()` with information about data points.

**Methods**

No methods found in currently loaded packages.

**Note**

For available methods, see- [https://indrajeetpatil.github.io/broomExtra/articles/available\\_methods.html](https://indrajeetpatil.github.io/broomExtra/articles/available_methods.html)

**Author(s)**

Indrajeet Patil

**See Also**

`grouped_augment`, `augment`

**Examples**

```
set.seed(123)

# example-1: linear model
broomExtra::boot_augment(
  data = mtcars,
  times = 10,
  ..f = stats::lm,
  formula = mpg ~ wt,
  na.action = na.omit
)

# example-2: linear mixed-effects model
library(lme4)

broomExtra::boot_augment(
  data = sleepstudy,
  times = 25,
  ..f = lme4::lmer,
  formula = Reaction ~ Days + (Days | Subject)
)
```

---

boot\_glance

*Bootstrapped dataframe with model summaries from each sample.*

---

**Description**

Bootstrapped dataframe with model summaries from each sample.

**Usage**

```
boot_glance(data, times = 25, strata = NULL, apparent = FALSE, ..f,
  ...)
```

**Arguments**

data	Dataframe (or tibble) from which variables are to be taken.
times	The number of bootstrap samples.
strata	A variable that is used to conduct stratified sampling. When not NULL, each bootstrap sample is created within the stratification variable. This could be a single character value or a variable name that corresponds to a variable that exists in the data frame.
apparent	A logical. Should an extra resample be added where the analysis and holdout subset are the entire data set. This is required for some estimators used by the summary function that require the apparent error rate.
..f	A function, or function name as a string.
...	Arguments to function. These dots support <a href="#">tidy-dots</a> features.

**Methods**

No methods found in currently loaded packages.

**Note**

For available methods, see- [https://indrajeetpatil.github.io/broomExtra/articles/available\\_methods.html](https://indrajeetpatil.github.io/broomExtra/articles/available_methods.html)

**Author(s)**

[Indrajeet Patil](#)

**See Also**

[grouped\\_glance](#), [glance](#)

**Examples**

```
set.seed(123)

# example-1: linear model
broomExtra::boot_glance(
  data = mtcars,
  times = 500,
  ..f = stats::lm,
  formula = mpg ~ wt,
  na.action = na.omit
)

# example-2: linear mixed-effects model
library(lme4)

broomExtra::boot_glance(
  data = sleepstudy,
  times = 25,
  ..f = lme4::lmer,
  formula = Reaction ~ Days + (Days | Subject)
)
```

boot\_tidy

*Bootstrapped dataframe with estimates from each sample.***Description**

Bootstrapped dataframe with estimates from each sample.

**Usage**

```
boot_tidy(data, times = 25, strata = NULL, apparent = FALSE, ..f,
  ..., tidy.args = list())
```

**Arguments**

data	Dataframe (or tibble) from which variables are to be taken.
times	The number of bootstrap samples.
strata	A variable that is used to conduct stratified sampling. When not NULL, each bootstrap sample is created within the stratification variable. This could be a single character value or a variable name that corresponds to a variable that exists in the data frame.
apparent	A logical. Should an extra resample be added where the analysis and holdout subset are the entire data set. This is required for some estimators used by the summary function that require the apparent error rate.
..f	A function, or function name as a string.
...	Arguments to function. These dots support <a href="#">tidy-dots</a> features.
tidy.args	A list of arguments to be used in the relevant S3 method.

**Value**

A `tibble::tibble()` with information about model components.

**Methods**

No methods found in currently loaded packages.

**Note**

For available methods, see- [https://indrajeetpatil.github.io/broomExtra/articles/available\\_methods.html](https://indrajeetpatil.github.io/broomExtra/articles/available_methods.html)

**Author(s)**

Indrajeet Patil

**See Also**

[grouped\\_tidy](#), [tidy](#)

**Examples**

```

set.seed(123)

# example-1: linear model
broomExtra::boot_tidy(
  data = mtcars,
  times = 500,
  ..f = stats::lm,
  formula = mpg ~ wt,
  na.action = na.omit,
  tidy.args = list(conf.int = TRUE, conf.level = 0.50)
)

# example-2: linear mixed-effects model
library(lme4)

broomExtra::boot_tidy(
  data = sleepstudy,
  times = 25,
  ..f = lme4::lmer,
  formula = Reaction ~ Days + (Days | Subject),
  tidy.args = list(effects = "fixed")
)

```

glance

*Retrieve model summary dataframe if it exists.***Description**

Check if a glance method exists for a given object, either in broom or in broom.mixed. If it does, return the model summary dataframe, if not, return a NULL.

**Usage**

```
glance(x, ...)
```

**Arguments**

x	model or other R object to convert to single-row data frame
...	other arguments passed to methods

**Methods**

No methods found in currently loaded packages.

**Note**

For available methods, see- [https://indrajeetpatil.github.io/broomExtra/articles/available\\_methods.html](https://indrajeetpatil.github.io/broomExtra/articles/available_methods.html)

**Author(s)**

Indrajeet Patil

**See Also**

[grouped\\_glance](#), [boot\\_glance](#)

**Examples**

```
set.seed(123)
library(lme4)

# mixed-effects models (`broom.mixed` will be used)
lmm.mod <- lmer(Reaction ~ Days + (Days | Subject), sleepstudy)
broomExtra::glance(lmm.mod)

# linear model (`broom` will be used)
lm.mod <- lm(Reaction ~ Days, sleepstudy)
broomExtra::glance(lm.mod)
```

---

grouped_augment	<i>Augmented data from grouped analysis of any function that has data argument in its function call.</i>
-----------------	--

---

**Description**

Augmented data from grouped analysis of any function that has data argument in its function call.

**Usage**

```
grouped_augment(data, grouping.vars, ..f, ..., augment.args = list())
```

**Arguments**

data	Dataframe (or tibble) from which variables are to be taken.
grouping.vars	Grouping variables.
..f	A function, or function name as a string.
...	Arguments to function. These dots support <a href="#">tidy-dots</a> features.
augment.args	A list of arguments to be used in the relevant S3 method.

**Value**

A [tibble::tibble\(\)](#) with information about data points.

**Methods**

No methods found in currently loaded packages.

**Note**

For available methods, see- [https://indrajeetpatil.github.io/broomExtra/articles/available\\_methods.html](https://indrajeetpatil.github.io/broomExtra/articles/available_methods.html)



**Author(s)**

Indrajeet Patil

**See Also**[augment](#), [boot\\_augment](#)**Examples**

```

set.seed(123)
# to speed up computation, let's use only 50% of the data

# linear model
broomExtra::grouped_augment(
  data = dplyr::sample_frac(tbl = ggplot2::diamonds, size = 0.5),
  grouping.vars = c(cut, color),
  formula = price ~ carat - 1,
  ..f = stats::lm,
  na.action = na.omit,
  augment.args = list(se_fit = TRUE)
)

# linear mixed effects model
broomExtra::grouped_augment(
  data = dplyr::sample_frac(tbl = ggplot2::diamonds, size = 0.5),
  grouping.vars = cut,
  ..f = lme4::lmer,
  formula = price ~ carat + (carat | color) - 1,
  control = lme4::lmerControl(optimizer = "bobyqa")
)

```

grouped\_glance

*Model summary output from grouped analysis of any function that has data argument in its function call.*

**Description**

Model summary output from grouped analysis of any function that has data argument in its function call.

**Usage**

```
grouped_glance(data, grouping.vars, ..f, ...)
```

**Arguments**

data	Dataframe (or tibble) from which variables are to be taken.
grouping.vars	Grouping variables.
..f	A function, or function name as a string.
...	Arguments to function.
	These dots support <a href="#">tidy-dots</a> features.

**Methods**

No methods found in currently loaded packages.

**Note**

For available methods, see- [https://indrajeetpatil.github.io/broomExtra/articles/available\\_methods.html](https://indrajeetpatil.github.io/broomExtra/articles/available_methods.html)

**Author(s)**

Indrajeet Patil

**See Also**

[glance](#), [boot\\_glance](#)

**Examples**

```
set.seed(123)
# to speed up computation, let's use only 50% of the data

# linear model
broomExtra::grouped_glance(
  data = dplyr::sample_frac(tbl = ggplot2::diamonds, size = 0.5),
  grouping.vars = c(cut, color),
  formula = price ~ carat - 1,
  ..f = stats::lm,
  na.action = na.omit
)

# linear mixed effects model
broomExtra::grouped_glance(
  data = dplyr::sample_frac(tbl = ggplot2::diamonds, size = 0.5),
  grouping.vars = cut,
  ..f = lme4::lmer,
  formula = price ~ carat + (carat | color) - 1,
  control = lme4::lmerControl(optimizer = "bobyqa")
)
```

---

grouped\_tidy

*Tidy output from grouped analysis of any function that has data argument in its function call.*

---

**Description**

Tidy output from grouped analysis of any function that has data argument in its function call.

**Usage**

```
grouped_tidy(data, grouping.vars, ..f, ..., tidy.args = list())
```

**Arguments**

<code>data</code>	Dataframe (or tibble) from which variables are to be taken.
<code>grouping.vars</code>	Grouping variables.
<code>..f</code>	A function, or function name as a string.
<code>...</code>	Arguments to function. These dots support <a href="#">tidy-dots</a> features.
<code>tidy.args</code>	A list of arguments to be used in the relevant S3 method.

**Value**

A `tibble::tibble()` with information about model components.

**Methods**

No methods found in currently loaded packages.

**Note**

For available methods, see- [https://indrajeetpatil.github.io/broomExtra/articles/available\\_methods.html](https://indrajeetpatil.github.io/broomExtra/articles/available_methods.html)

**Author(s)**

Indrajeet Patil

**See Also**

[tidy](#), [boot\\_tidy](#)

**Examples**

```
set.seed(123)
# to speed up computation, let's use only 50% of the data

# linear model
broomExtra::grouped_tidy(
  data = dplyr::sample_frac(tbl = ggplot2::diamonds, size = 0.5),
  grouping.vars = c(cut, color),
  formula = price ~ carat - 1,
  ..f = stats::lm,
  na.action = na.omit,
  tidy.args = list(quick = TRUE)
)

# linear mixed effects model
broomExtra::grouped_tidy(
  data = dplyr::sample_frac(tbl = ggplot2::diamonds, size = 0.5),
  grouping.vars = cut,
  ..f = lme4::lmer,
  formula = price ~ carat + (carat | color) - 1,
  control = lme4::lmerControl(optimizer = "bobyqa"),
  tidy.args = list(conf.int = TRUE, conf.level = 0.99)
)
```

tidy

*Retrieve tidy dataframe if it exists.***Description**

Checks if a tidy method exists for a given object, either in broom or in broom.mixed. If it does, it turn an object into a tidy tibble, if not, return a NULL. In case of data frames, a tibble data frame is returned.

**Usage**

```
tidy(x, ...)
```

**Arguments**

`x`                      An object to be converted into a tidy `tibble::tibble()`.  
`...`                    Additional arguments to tidying method.

**Value**

A `tibble::tibble()` with information about model components.

**Methods**

No methods found in currently loaded packages.

**Note**

For available methods, see- [https://indrajeetpatil.github.io/broomExtra/articles/available\\_methods.html](https://indrajeetpatil.github.io/broomExtra/articles/available_methods.html)

**Author(s)**

Indrajeet Patil

**See Also**

`grouped_tidy`, `boot_tidy`

**Examples**

```
set.seed(123)
library(lme4)

# mixed-effects models (`broom.mixed` will be used)
lmm.mod <- lmer(Reaction ~ Days + (Days | Subject), sleepstudy)
broomExtra::tidy(x = lmm.mod, effects = "fixed", exponentiate = TRUE)

# linear model (`broom` will be used)
lm.mod <- lm(Reaction ~ Days, sleepstudy)
broomExtra::tidy(x = lm.mod, conf.int = TRUE)

# unsupported object (the function will return `NULL` in such cases)
broomExtra::tidy(list(1, c("x", "y")))
```

# Index

augment, [2](#), [4](#), [9](#)

boot\_augment, [3](#), [3](#), [9](#)

boot\_glance, [4](#), [8](#), [10](#)

boot\_tidy, [6](#), [11](#), [12](#)

glance, [5](#), [7](#), [10](#)

grouped\_augment, [3](#), [4](#), [8](#)

grouped\_glance, [5](#), [8](#), [9](#)

grouped\_tidy, [6](#), [10](#), [12](#)

tibble::tibble(), [2](#), [4](#), [6](#), [8](#), [11](#), [12](#)

tidy, [6](#), [11](#), [12](#)

tidy-dots, [3](#), [5](#), [6](#), [8](#), [9](#), [11](#)