

Package ‘glyph’

July 6, 2026

Title A Next-Generation Grammar of Interactive Graphics

Version 0.1.0

Description A modern visualization grammar that treats interactivity, animation, and composable layouts as first-class concepts rather than afterthoughts. Designed to address key limitations of existing grammars: native hover, click, and zoom events, 'WebGL'-accelerated rendering for large datasets, built-in multi-plot composition, and a token-based theming system. Renders to interactive HTML widgets via 'D3.js' or static SVG from a single declarative specification.

License MIT + file LICENSE

Encoding UTF-8

Depends R (>= 4.1.0)

RoxygenNote 7.3.3

Config/testthat/edition 3

Imports htmlwidgets (>= 1.6.0), jsonlite (>= 1.8.0), rlang (>= 1.1.0), cli (>= 3.6.0), grDevices, utils, tools

Suggests testthat (>= 3.0.0), knitr, rmarkdown

VignetteBuilder knitr

URL <https://github.com/josh45-source/glyph>

BugReports <https://github.com/josh45-source/glyph/issues>

NeedsCompilation no

Author Joash Joshua Ayo [aut, cre]

Maintainer Joash Joshua Ayo <joashjoshua789@gmail.com>

Repository CRAN

Date/Publication 2026-07-06 12:30:08 UTC

Contents

animate	2
animation	3
compile	4
compose	5
export	6
facet	6
glyph	7
inset	7
interact	8
interactivity	9
layout	9
marginals	10
marks	10
mark_area	11
mark_bar	11
mark_line	12
mark_link	12
mark_point	13
mark_ribbon	13
mark_rule	14
mark_text	15
print.glyph_spec	15
render	16
rendering	16
scale	17
scales	18
selection	19
theme_tokens	20
theming	21
titles	21
to_vegalite	22
Index	23

 animate

Add animation/transition behavior

Description

Add animation/transition behavior

Usage

```
animate(
  spec,
  transition = "morph",
  duration = 500,
  stagger = 0,
  by = NULL,
  easing = "ease-in-out",
  loop = FALSE
)
```

Arguments

spec	A <code>glyph_spec</code>
transition	Transition type: "morph", "fade", "slide", "none"
duration	Duration in milliseconds
stagger	Delay between successive marks in ms (for entrance effects)
by	Column that defines animation keyframes (like <code>gganimate</code> 's <code>transition_states</code>). e.g. <code>by = year</code> plays through years.
easing	Easing function: "linear", "ease-in", "ease-out", "ease-in-out", "bounce", "elastic"
loop	Repeat animation (TRUE, FALSE, or number of times)

Value

Modified `glyph_spec`

Examples

```
# Entrance animation: bars grow from baseline
glyph(mtcars, x = cyl, y = mpg) |>
  mark_bar() |>
  animate(transition = "slide", stagger = 50)

# Keyframe animation: morph between groups
glyph(mtcars, x = wt, y = mpg) |>
  mark_point(size = hp, color = cyl) |>
  animate(by = gear, transition = "morph", duration = 800)
```

Description

Animations in `glyph` are declarative state transitions, not frame-by-frame rendering. You describe *what changes* and *how it should interpolate*, and the renderer handles the rest.

Details

Two animation paradigms:

- **Transitions:** animate between data states (e.g. year 2020 → 2021). Marks morph smoothly, entering/exiting as data changes.
- **Entrances:** animate marks appearing on first render (stagger bars growing from zero, points fading in).

compile

Compile a glyph spec to a resolved representation

Description

Compile a glyph spec to a resolved representation

Usage

```
compile(spec, engine = "auto", width = NULL, height = NULL)
```

```
## S3 method for class 'glyph_spec'
compile(spec, engine = "auto", width = NULL, height = NULL)
```

```
## S3 method for class 'glyph_layout'
compile(spec, engine = "auto", width = NULL, height = NULL)
```

Arguments

spec	A <code>glyph_spec</code> or <code>glyph_layout</code>
engine	Rendering backend: "auto", "html", "svg", "canvas", "webgl"
width	Width in pixels (NULL for auto)
height	Height in pixels (NULL for auto)

Value

A `glyph_compiled` object (a list with resolved data + JSON)

A `glyph_compiled` object containing the resolved spec, JSON string, and engine selection

A `glyph_compiled` object containing the resolved layout spec and JSON string

`compose`*Compose multiple glyph specs into a layout*

Description

Compose multiple glyph specs into a layout

Usage

```
compose(  
  ...,  
  type = "hstack",  
  widths = NULL,  
  heights = NULL,  
  gap = 10,  
  shared_scales = FALSE,  
  linked_selections = FALSE,  
  title = NULL  
)
```

Arguments

<code>...</code>	glyph_spec objects or layout objects (for nesting)
<code>type</code>	Layout type: "hstack", "vstack", "grid", "wrap"
<code>widths</code>	Relative widths for columns (e.g. <code>c(2, 1)</code> for 2:1 split)
<code>heights</code>	Relative heights for rows
<code>gap</code>	Gap between plots in px
<code>shared_scales</code>	Share axis scales across plots: TRUE, FALSE, "x", "y", or "both"
<code>linked_selections</code>	Share interaction selections across plots
<code>title</code>	Overall layout title

Value

A `glyph_layout` object

Examples

```
p1 <- glyph(mtcars, x = wt, y = mpg) |> mark_point()  
p2 <- glyph(mtcars, x = wt, y = hp) |> mark_point()  
p3 <- glyph(mtcars, x = hp, y = mpg) |> mark_line()  
  
# Horizontal stack  
compose(p1, p2, type = "hstack")  
  
# Grid with linked brushing
```

```
compose(p1, p2, p3, type = "wrap",
        linked_selections = TRUE, shared_scales = "x")
```

export *Export to various formats*

Description

Export to various formats

Usage

```
export(spec, file, width = 800, height = 600)
```

Arguments

spec	A <code>glyph_spec</code> or <code>glyph_compiled</code>
file	Output file path. Extension determines format: <code>.html</code> , <code>.svg</code> , <code>.png</code> , <code>.pdf</code> , <code>.json</code> (exports the raw spec)
width	Width in pixels
height	Height in pixels

Value

Invisibly returns the output file path

facet *Facet a plot by one or two variables*

Description

Like `ggplot2`'s `facet_wrap`/`facet_grid` but with a key improvement: each facet can have independent geom parameters and scales by default (instead of forced uniformity).

Usage

```
facet(spec, rows = NULL, cols = NULL, free_scales = "none", wrap = NULL)
```

Arguments

spec	A <code>glyph_spec</code>
rows	Row faceting variable (bare name or <code>NULL</code>)
cols	Column faceting variable (bare name or <code>NULL</code>)
free_scales	"none", "x", "y", "both"
wrap	If only one variable, wrap into a grid with this many columns

Value

Modified `glyph_spec`

glyph	<i>Create a Glyph Visualization</i>
-------	-------------------------------------

Description

Entry point for the `glyph` grammar. Creates a specification object that describes a visualization declaratively. Unlike `ggplot2`, the `spec` is a pure data structure (nested list) that can be serialized, inspected, and compiled to multiple backends.

Usage

```
glyph(data = NULL, ...)
```

Arguments

<code>data</code>	A <code>data.frame</code> or <code>tibble</code> . Unlike <code>ggplot2</code> , <code>glyph</code> also accepts lists-of-lists, URLs to CSV/JSON, or arrow tables (planned).
<code>...</code>	Global aesthetic mappings using bare column names (no <code>aes()</code> needed). e.g. <code>glyph(mtcars, x = wt, y = mpg)</code>

Value

A `glyph_spec` object

Examples

```
spec <- glyph(mtcars, x = wt, y = mpg) |>
  mark_point()
summary(spec)
```

inset	<i>Add an inset plot</i>
-------	--------------------------

Description

Add an inset plot

Usage

```
inset(spec, inset, position = "top-right")
```

Arguments

spec	The main <code>glyph_spec</code>
inset	A <code>glyph_spec</code> to place as an inset
position	Where to place: "top-right", "top-left", "bottom-right", "bottom-left", or a list(x, y, width, height) with proportions 0-1

Value

Modified `glyph_spec`

interact	<i>Add interactive behaviors to a <code>glyph_spec</code></i>
----------	---

Description

Add interactive behaviors to a `glyph_spec`

Usage

```
interact(
  spec,
  tooltip = FALSE,
  zoom = FALSE,
  brush = FALSE,
  hover = NULL,
  click = NULL,
  crossfilter = FALSE,
  nearest = FALSE
)
```

Arguments

spec	A <code>glyph_spec</code>
tooltip	Show values on hover. TRUE for auto-generated, or a glue-style template string like "{x}: {y} ({color})".
zoom	Enable scroll-to-zoom and pan
brush	Enable rectangular brush selection
hover	Highlight mark on hover ("enlarge", "brighten", "outline", or NULL)
click	Action on click: "select", "filter", "url", or a callback name
crossfilter	Link this plot's selections to other plots in a layout
nearest	Snap selection to nearest point (useful for line charts)

Value

Modified `glyph_spec`

Examples

```
glyph(mtcars, x = wt, y = mpg) |>
  mark_point(color = cyl) |>
  interact(
    tooltip = "{cyl} cylinders\n{mpg} mpg at {wt} tons",
    zoom = TRUE,
    hover = "enlarge",
    brush = TRUE,
    crossfilter = TRUE
  )
```

interactivity

First-Class Interactivity

Description

Unlike ggplot2 where interactivity is bolted on via ggplotly(), glyph treats interaction as part of the visualization grammar. Interactions are declared in the spec and compiled to the appropriate backend (D3 events for HTML, Shiny bindings for server-side).

Details

Design philosophy: interactions are *selections* that filter or highlight marks. This follows Vega-Lite's insight that most interactions are really about defining subsets of the data. A tooltip is "select the nearest point, show its values." Brushing is "select points in a rectangle, highlight them."

layout

Layout Composition

Description

Built-in multi-plot composition. No external packages needed. Layouts can express grids, stacks, insets, marginal plots, and arbitrary nesting. Composed plots can share selections for cross-filtering (linked brushing).

marginals	<i>Add a marginal plot (histogram/density on axes)</i>
-----------	--

Description

Adds marginal distributions to a plot's axes — a common pattern that requires `ggExtra` or manual grid manipulation in `ggplot2`.

Usage

```
marginals(spec, x = "histogram", y = "histogram", size = 0.15)
```

Arguments

<code>spec</code>	A <code>glyph_spec</code>
<code>x</code>	Marginal type for x-axis: "histogram", "density", "boxplot", NULL
<code>y</code>	Marginal type for y-axis: "histogram", "density", "boxplot", NULL
<code>size</code>	Proportion of plot area for marginals (0.0 to 0.4)

Value

Modified `glyph_spec`

Examples

```
glyph(mtcars, x = wt, y = mpg) |>
  mark_point(color = cyl) |>
  marginals(x = "histogram", y = "density")
```

marks	<i>Visual Marks</i>
-------	---------------------

Description

Marks are the visual encodings in `glyph` — analogous to `ggplot2`'s `geoms` but with key differences:

1. **Mappings without `aes()`**: pass bare column names directly.
2. **Per-mark data**: each mark can have its own data source, enabling multi-dataset plots without awkward data parameter overrides.
3. **Built-in interaction hints**: marks carry interaction metadata (what happens on hover, click, drag) as part of the spec.
4. **Transition-aware**: marks know how to interpolate between states for animation.

mark_area	<i>Add an area mark</i>
-----------	-------------------------

Description

Add an area mark

Usage

```
mark_area(spec, ..., data = NULL, style = list())
```

Arguments

spec	A <code>glyph_spec</code>
...	Aesthetic mappings (x, y, color, size, shape, alpha, tooltip)
data	Optional per-mark data override
style	Named list of fixed visual properties

Value

Modified `glyph_spec` object with the area mark added

mark_bar	<i>Add a bar mark</i>
----------	-----------------------

Description

Add a bar mark

Usage

```
mark_bar(spec, ..., data = NULL, style = list(), orient = "vertical")
```

Arguments

spec	A <code>glyph_spec</code>
...	Aesthetic mappings (x, y, color, size, shape, alpha, tooltip)
data	Optional per-mark data override
style	Named list of fixed visual properties
orient	"vertical" or "horizontal"

Value

Modified `glyph_spec` object with the bar mark added

mark_line	<i>Add a line mark</i>
-----------	------------------------

Description

Add a line mark

Usage

```
mark_line(spec, ..., data = NULL, style = list(), interpolate = "monotone")
```

Arguments

spec	A <code>glyph_spec</code>
...	Aesthetic mappings (x, y, color, size, shape, alpha, tooltip)
data	Optional per-mark data override
style	Named list of fixed visual properties
interpolate	Interpolation method: "linear", "monotone", "step", "basis"

Value

Modified `glyph_spec` object with the line mark added

mark_link	<i>Add a link/edge mark (for networks, sankeys, slope graphs)</i>
-----------	---

Description

Add a link/edge mark (for networks, sankeys, slope graphs)

Usage

```
mark_link(spec, ..., data = NULL, style = list())
```

Arguments

spec	A <code>glyph_spec</code>
...	Aesthetic mappings (x, y, color, size, shape, alpha, tooltip)
data	Optional per-mark data override
style	Named list of fixed visual properties

Value

Modified `glyph_spec` object with the link mark added

mark_point	<i>Add a point mark (scatterplot)</i>
------------	---------------------------------------

Description

Add a point mark (scatterplot)

Usage

```
mark_point(spec, ..., data = NULL, style = list())
```

Arguments

spec	A glyph_spec
...	Aesthetic mappings (x, y, color, size, shape, alpha, tooltip)
data	Optional per-mark data override
style	Named list of fixed visual properties

Value

Modified glyph_spec

Examples

```
spec <- glyph(mtcars, x = wt, y = mpg) |>  
mark_point(color = cyl, size = hp, tooltip = "{cyl} cyl, {mpg} mpg")
```

mark_ribbon	<i>Add a ribbon/band mark (for confidence intervals, ranges)</i>
-------------	--

Description

Add a ribbon/band mark (for confidence intervals, ranges)

Usage

```
mark_ribbon(spec, ..., data = NULL, style = list())
```

Arguments

spec	A glyph_spec
...	Aesthetic mappings (x, y, color, size, shape, alpha, tooltip)
data	Optional per-mark data override
style	Named list of fixed visual properties

Value

Modified `glyph_spec` object with the ribbon mark added

mark_rule	<i>Add a rule (reference line) mark</i>
-----------	---

Description

Add a rule (reference line) mark

Usage

```
mark_rule(
  spec,
  ...,
  data = NULL,
  style = list(),
  x_intercept = NULL,
  y_intercept = NULL
)
```

Arguments

spec	A <code>glyph_spec</code>
...	Aesthetic mappings (x, y, color, size, shape, alpha, tooltip)
data	Optional per-mark data override
style	Named list of fixed visual properties
x_intercept	Fixed x position for vertical rule
y_intercept	Fixed y position for horizontal rule

Value

Modified `glyph_spec` object with the rule mark added

mark_text	<i>Add a text/label mark</i>
-----------	------------------------------

Description

Add a text/label mark

Usage

```
mark_text(spec, ..., data = NULL, style = list(), smart_repel = TRUE)
```

Arguments

spec	A <code>glyph_spec</code>
...	Aesthetic mappings (x, y, color, size, shape, alpha, tooltip)
data	Optional per-mark data override
style	Named list of fixed visual properties
smart_repel	Automatically avoid label overlaps (TRUE by default). This is a first-class feature, not an extension package.

Value

Modified `glyph_spec` object with the text mark added

<code>print.glyph_spec</code>	<i>Auto-render when printed (like ggplot2)</i>
-------------------------------	--

Description

Auto-render when printed (like ggplot2)

Usage

```
## S3 method for class 'glyph_spec'
print(x, ...)
```

Arguments

x	A <code>glyph_spec</code> object
...	Additional arguments (ignored)

Value

Invisibly returns the `glyph_spec` object

render	<i>Render a glyph spec as an htmlwidget</i>
--------	---

Description

Render a glyph spec as an htmlwidget

Usage

```
render(spec, width = NULL, height = NULL)
```

Arguments

spec	A <code>glyph_spec</code> , <code>glyph_layout</code> , or <code>glyph_compiled</code>
width	Widget width
height	Widget height

Value

An `htmlwidget` object that renders the visualization in an HTML viewer

rendering	<i>Rendering Pipeline</i>
-----------	---------------------------

Description

The rendering pipeline compiles a `glyph_spec` into output. The spec is first resolved (evaluate quosures, compute stats, merge defaults), then serialized to JSON, then handed to a backend:

- **"html"** (default): `htmlwidgets` + `D3.js` for interactive viewing
- **"svg"**: Static SVG file (publication quality)
- **"canvas"**: HTML5 Canvas for large-data performance
- **"webgl"**: WebGL via `regl/deck.gl` for 100K+ points (planned)
- **"pdf"**: Direct PDF output via R's `pdf()` device (planned)

Details

Key architectural difference from `ggplot2`: the spec is a pure data structure. The `compile()` step resolves it into a concrete render tree. This means you can:

- Inspect the compiled spec as JSON (for debugging or export)
- Serialize it and render on a different machine
- Export it to Vega-Lite JSON (near 1:1 mapping)
- Compile to multiple backends from one spec

scale	<i>Define a scale for an aesthetic channel</i>
-------	--

Description

Define a scale for an aesthetic channel

Usage

```
scale(
  spec,
  aesthetic,
  type = "auto",
  domain = NULL,
  range = NULL,
  nice = TRUE,
  zero = FALSE,
  reverse = FALSE,
  label = NULL,
  format = NULL
)
```

Arguments

spec	A <code>glyph_spec</code>
aesthetic	Which channel: "x", "y", "color", "size", "shape", "alpha"
type	Scale type: "linear", "log", "sqrt", "time", "ordinal", "band", "quantize", "threshold"
domain	Explicit domain (data range). NULL for auto.
range	Explicit output range. For color: a palette name or vector.
nice	Round domain to nice values (TRUE/FALSE)
zero	Force zero in domain (TRUE/FALSE)
reverse	Reverse the scale
label	Axis/legend label (NULL for auto from column name)
format	Format string for tick labels (e.g. "%.2f", "%b %Y")

Value

Modified `glyph_spec`

Examples

```
glyph(mtcars, x = wt, y = mpg) |>
  mark_point(color = cyl) |>
  scale("y", "linear", zero = TRUE, label = "Miles per gallon") |>
  scale("color", "ordinal", range = "Set2")
```

scales

Scales

Description

Scales map data values to visual properties. Glyph simplifies ggplot2's `scale_<aesthetic>_<type>` explosion into a composable system: `scale(<aesthetic>, <type>, ...)`.

Usage

```
scale_color(spec, palette = "Tableau10", ...)
```

```
scale_log(spec, aesthetic = "y", base = 10, ...)
```

```
scale_time(spec, aesthetic = "x", ...)
```

Arguments

<code>spec</code>	A <code>glyph_spec</code>
<code>palette</code>	A named palette: "viridis", "Set2", "Tableau10", "Blues", etc.
<code>...</code>	Additional arguments passed to <code>scale()</code>
<code>aesthetic</code>	Which channel: "x", "y", "color", "size", "shape", "alpha"
<code>base</code>	Log base (default 10)

Value

Modified `glyph_spec` object

Modified `glyph_spec` object

Modified `glyph_spec` object

Functions

- `scale_color()`: Set color palette by name
- `scale_log()`: Log-transform an axis
- `scale_time()`: Time/date axis

selection	<i>Add a selection parameter (advanced)</i>
-----------	---

Description

For complex interactions: define a named selection that can be referenced by marks and scales. This is how you build linked views, conditional encoding, and interactive legends.

Usage

```
selection(  
  spec,  
  name,  
  type = "point",  
  on = "click",  
  fields = NULL,  
  resolve = "global"  
)
```

Arguments

spec	A <code>glyph_spec</code>
name	Selection name (referenced in conditional encodings)
type	"point", "interval", or "legend"
on	Event trigger: "click", "mouseover", "drag"
fields	Which data fields the selection projects onto
resolve	For composed views: "global", "union", "intersect"

Value

Modified `glyph_spec`

Examples

```
# Interactive legend: click legend entries to filter  
glyph(mtcars, x = wt, y = mpg) |>  
  mark_point(color = cyl) |>  
  selection("legend_filter", type = "legend", fields = "cyl")
```

 theme_tokens

Set theme tokens

Description

Set theme tokens

Usage

```
theme_tokens(
  spec,
  preset = NULL,
  font = NULL,
  font_size = NULL,
  bg = NULL,
  fg = NULL,
  accent = NULL,
  grid = NULL,
  border = NULL,
  padding = NULL,
  title_size = NULL
)
```

Arguments

spec	A <code>glyph_spec</code>
preset	A named preset: "light" (default), "dark", "minimal", "publication", "presentation". Presets set all tokens to coherent defaults.
font	Font family for all text
font_size	Base font size in px (axis labels scale relative to this)
bg	Background color
fg	Primary text/axis color
accent	Primary accent color (used for single-series marks)
grid	Grid line visibility: TRUE, FALSE, "x", "y"
border	Plot border: TRUE/FALSE
padding	Padding around the plot area in px
title_size	Title font size multiplier (relative to font_size)

Value

Modified `glyph_spec`

Examples

```

glyph(mtcars, x = wt, y = mpg) |>
  mark_point() |>
  theme_tokens(preset = "dark")

glyph(mtcars, x = wt, y = mpg) |>
  mark_point() |>
  theme_tokens(font = "IBM Plex Sans", bg = "#fafafa", grid = "y")

```

theming	<i>Token-Based Theming</i>
---------	----------------------------

Description

Instead of ggplot2's 90+ theme() arguments, glyph uses a design-token system. A small set of semantic tokens (font, colors, spacing, sizes) cascade through the entire visualization. Think of it like CSS custom properties for plots.

Details

Tokens cascade: setting bg changes the background, but also automatically adjusts text color for contrast, grid line opacity, and tooltip styling. You override only what you want; everything else adapts.

titles	<i>Add a title, subtitle, or caption</i>
--------	--

Description

Add a title, subtitle, or caption

Usage

```
titles(spec, title = NULL, subtitle = NULL, caption = NULL)
```

Arguments

spec	A glyph_spec
title	Main title
subtitle	Subtitle (below title)
caption	Caption (bottom of plot, for source attribution)

Value

Modified glyph_spec object with updated title metadata

to_vegalite	<i>Export the spec as Vega-Lite JSON (interop)</i>
-------------	--

Description

Because glyph's spec is structurally similar to Vega-Lite, we can export to Vega-Lite JSON for use in Python (Altair), JavaScript, or the Vega Editor.

Usage

```
to_vegalite(spec)
```

Arguments

spec	A glyph_spec
------	--------------

Value

A JSON string in Vega-Lite format

Index

animate, [2](#)
animation, [3](#)

compile, [4](#)
compose, [5](#)

export, [6](#)

facet, [6](#)

glyph, [7](#)

inset, [7](#)
interact, [8](#)
interactivity, [9](#)

layout, [9](#)

marginals, [10](#)
mark_area, [11](#)
mark_bar, [11](#)
mark_line, [12](#)
mark_link, [12](#)
mark_point, [13](#)
mark_ribbon, [13](#)
mark_rule, [14](#)
mark_text, [15](#)
marks, [10](#)

print.glyph_spec, [15](#)

render, [16](#)
rendering, [16](#)

scale, [17](#)
scale_color (scales), [18](#)
scale_log (scales), [18](#)
scale_time (scales), [18](#)
scales, [18](#)
selection, [19](#)

theme_tokens, [20](#)

theming, [21](#)
titles, [21](#)
to_vegalite, [22](#)